



SL NO	SHELL SIZE	A	B
1	09	30.80	25.00
2	15	39.15	33.30
3	25	53.05	47.00
4	37	69.30	63.50

PART NUMBER LOGIC

TBDSC-	L	A	09	P	C
--------	---	---	----	---	---

BASIC SERIES
L- NICKEL PLATING
CONTACT SIZE
A-20 SIZE CONTACT (STANDARD DENSITY)
INSERT ARRANGEMENT
09,15,25 & 37 - STANDARD DENSITY LAYOUT
P-PIN
A- WITHOUT CRIMP PIN CONTACT
C - CRIMP

NOTE :

1. SHELL : PLATED STEEL
2. INSULATOR : TEHRMOPLASTIC (PBT)
3. CONTACT : COPPER ALLOY (GOLD PLATED)
4. CURRENT RATING : 7.5AMP
5. DIELECTRIC : 1000Vrms
6. INSULATION RESISTANCE : 1000MΩ Min (at 500V DC)

THIS DOCUMENT IS SOLE PROPERTY AND IS ISSUED IN STRICT CONFIDENCE THAT IT WILL NOT BE REPRODUCED IN ANY WAY OR USED TO SOLICIT BUSINESS OF A COMPETITIVE NATURE. DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED UNLESS WRITTEN CONSENT IS OBTAINED FROM TURBO INDIA. THIS DOCUMENT IS SUITABLE FOR ENGINEERING EVALUATION AND MAY BE USED IN TECHNICAL SPECIFICATIONS.	MATERIAL:	---	UNLESS OTHERWISE NOTED: DIMENSIONS ARE IN MM : FRACTION ARE ± 1/16 .XX DECIMALS ARE ± .25 .XXX DECIMALS ARE ± .07 ANGLES ARE ± 2° DO NOT SCALE THIS DRAWING	DESCRIPTION: DSUB PLUG CONNECTOR CRIMP TYPE STANDARD DENSITY	
	SURFACE AREA:	---			
	EST. WEIGHT:	---			
	DRAWN:	MS	DRAWING NUMBER: CRD-TBDSC-LAXXPC		REVISION: 0
	CHECKED:	SSC			
APPROVED:	SSC	SHEET 1 OF 1			
DATE:	25-01-2023				