
Product Specification

Part Name: 5.00 inch TFT Display Module
Customer Part ID: TLET0500B9-I (IPS)

1. Introduction

1.1 Scope of application

This specification applies to the LCD module that is supplied by Element Touch.

LCD specification: Dots 800xRGBx480.

As to basic specification of the driver IC, refer to the IC (ST7262H) specification and data book.

All material & processing of the LCD module should be Lead Free.

1.2 TFT features:

Structure: TFT PANNEL+IC +FPC+BL;

ALL O'CLOCK Type LCD

800dot-segment and 480 dot-common outputs;

16.7M Color can be selected by software;


White LED back light;

24 bit RGB interface

1.3 Applications:

2. LCM General specification

ITEM	Standard value	Unit
LCD Type	Normally black	--
Drive element	TFT active matrix	--
Number of pixels	800*3RGB(H)X480(V)	Dots
Pixel arrangement	RGB stripe	--
Pixel Pitch (W*H)	0.135 (H) x 0.135 (V)	mm
Active area	108 (H) x 64.8 (V)	mm
Viewing direction	ALL O'CLOCK	-
TFT Driver IC	ST7262H	
TFT interface	24 bit RGB Interface	-
Module Size(W*H*T)	120.74(W) ×75.84(H) ×3.00(T)	mm
Approx. Weight	TBD	g
Touch structure		
Touch Driver IC		-
Touch Interface		



3. Absolute Maximum Rating

Characteristics	Symbol	Min.	Max.	Unit
LCM Operating Temperature	T _{OPR}	-30	+80	°C
LCM Storage Temperature	T _{STG}	-30	+80	°C
Humidity	RH	-	90	%

4. Electrical Characteristics

4.1 TFT DC Characteristics

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Note
Supply Voltage for(DC/DC)	VDD	3.1	3.3	3.6	V	
TFT Gate ON Voltage	VGH	--	(15)	--	V	*1,*2
TFT Gate OFF Voltage	VGL	--	(-10)	--	V	
TFT Common Voltage	Vcom	--	(0)	--	V	
Data (RGB signal) Voltage	Vsig	(-5.5)	--	(5.5)	V	

Note:

*1. VGH is TFT Gate operating Voltage.

*2. VGL is TFT Gate operating Voltage.

The storage structure of this model is G_{ST}(Storage on Common)

*3. Vcom must be adjusted to optimize display quality _Cross talk, Contrast Ratio and etc.

4.2 Back-Light Unit Characteristics


The back-light system is an edge-lighting type with 18 white LEDs. The characteristics of the back-light are shown in the following tables.

Characteristics	Symbol	Min.	Type	Max.	Unit	Notes
Forward Voltage	V _F	16.5	--	17.4	V	-
Forward current	I _F	--	120	-	mA	-
Luminance(With LCD)	L _v		1000	--	cd/m ²	-
LED life time	N/A	----	20,000	--	Hr	Note 1

Note:

- (1) The “LED life time” is defined as the module brightness decrease to 50% of original brightness at I_L=20mA/LED. The LED life time could be decreased if operating I is larger than 25mA/LED.

Backlight circuit diagram shown in below:



5. Module Function Description


Pin No.	Symbol	Description
1	LEDK	POWER SUPPLY- FOR BACKLIGHT cathode
2	LEDA	POWER SUPPLY+ FOR BACKLIGHT ANODE
3	GND	GND
4	VDD	POWER SUPPLY
5~12	R0~R7	8 bit data bus display red data.
13~20	G0~G7	8 bit data bus display green data
21~28	B0~B7	8 bit data bus display blue data
29	GND	GND
30	DCLK	Pixel clock signal in RGB I/F
31	DISP	DISP=0: Standby mode (Default)、DISP=1: Normal display mode
32	HSYNC	Horizontal sync. Signal in RGB I/F
33	VSYNC	Vertical sync. Signal in RGB I/F
34	DE	Data enable signal in RGB I/F mode 1
35	NC	NC
36	GND	GND
37	XR (NC)	NC
38	YD (NC)	NC
39	XL (NC)	NC
40	YU (NC)	NC


6. Timing Characteristics

RGB Mode Selection Table	DCLK	HSYNC	VSYNC	DE
SYNC - DE Mode	Input	Input	Input	Input
SYNC Mode	Input	Input	Input	GND
DE Mode	Input	GND	GND	Input

Note: "Input" means these signals are driven by host side

DE Mode:



SYNC Mode:

Parallel 24-bit RGB Input Timing (PVDD=PVDD1=VDD=VDDI= 3.3V, AGND= 0V, TA=25°C)

Parallel 24-bit RGB Interface Timing Table							
Item	Symbol	Min.	Typ.	Max.	Unit	Remark	
DCLK Frequency		Fclk	23	25	27	MHz	
HSYNC	Period Time	Th	-	816	896	DCLK	
	Display Period	Thdisp		800		DCLK	
	Back Porch	Thbp	-	8	48	DCLK	
	Front Porch	Thfp	-	8	48	DCLK	
	Pulse Width	Thw	-	4	8	DCLK	
VSYNC	Period Time	Tv	-	496	504	HSYNC	
	Display Period	Tvdisp		480		HSYNC	
	Back Porch	Tvbp	-	8	12	HSYNC	
	Front Porch	Tvfp	-	8	12	HSYNC	
	Pulse Width	Tvw	-	4	8	HSYNC	

Note: The minimum blanking time depends on the GIP timing of the panel specification.

7. Optical Characteristics

7.1 Optical Specification

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note	
Transmittance (with Polarizer)	T (%)	$\Theta=0$ Normal viewing angle	—	(4.8)	—	%	Measuring with normal polarizer · Reference Only Base on Vop=5.1V	
Transmittance (without Polarizer)	T (%)		—	(16.2)	—	%		
Contrast Ratio	CR		(800)	(1000)	—	—	(1)(2)	
Response Time	T_{R+T_F}		—	30	40	msec	(1)(3)	
Color Gamut	(%)		45	50	—	%	C-light	
Color Chromaticity (CIE1931)	White		W_x	—	(0.320)	—	—	(1)(4) CF glass C-light
			W_y	—	(0.345)	—	—	
	Red		R_x	—	(0.629)	—	—	
			R_y	—	(0.326)	—	—	
	Green		G_x	—	(0.337)	—	—	
		G_y	—	(0.546)	—	—		
Blue	B_x	—	(0.136)	—	—			
	B_y	—	(0.143)	—	—			
Viewing Angle	Hor.	Θ_L	70	80	—	—	(1)(4) Measuring with normal polarizer · Reference Only	
		Θ_R	70	80	—			
	Ver.	Θ_U	70	80	—			
		Θ_D	70	80	—			
Optima View Direction	Free						(5)	


7.2 Measuring Condition

- Measuring surrounding: dark room
- Ambient temperature: $25 \pm 2^\circ\text{C}$
- 15min. warm-up time.

7.3 Measuring Equipment

- FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.


Note (1) Definition of Viewing Angle:




Note (2) Definition of Contrast Ratio (CR) :
measured at the center point of panel

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$


Note (3) Definition of Response Time : Sum of T_R and T_F



Note (4) Definition of optical measurement setup



Note (5) Rubbing Direction & Polarizer Absorption Direction



Item	Specifications	Unit	Note
Rubbing Direction	90° (TFT) / -90° (CF)	degree	2-domain IPS-pro
Absorption axis of Polarizer	90° (TFT) / 0° (CF)	degree	Array Film Up CF Film Down

8. Reliability Test Item

No.	Test Item	Test Condition	Notes
1	High Temp. Storage	+80°C / 240H	1. Functional test isOK. Missing Segment,short, unclear segment non-display,display abnormally and liquid crystal leakare un-allowed. 2. No low temperature bubbles,end seal loose andfall, frame rainbow.
2	Low Temp. Storage	-30°C / 240H	
3	High Tempe. Operating	+80°C / 240H	
4	Low Tempe. Operating	-30°C / 240H	
5	High Temperature /Humidity storage	60+5°C x 90%RH / 240 H	
6	Thermal and cold shock	Static state, -30°C 30min) ~80°C (30min) , 50 cycles	

9. Packing Method----TBD

- END -