



SL NO	SHELL SIZE	A	B
1	09	30.80	25.00
2	15	39.15	33.30
3	25	53.05	47.00
4	37	69.30	63.50

NOTE :

1. SHELL : PLATED STEEL
2. INSULATOR : TEHRMOPLASTIC (PBT)
3. CONTACT : COPPER ALLOY (GOLD PLATED)
4. CURRENT RATING : 7.5AMP
5. DIELECTRIC : 1000Vrms
6. INSULATION RESISTANCE : 1000MΩ Min (at 500V DC)

PART NUMBER LOGIC

TBDSC-	L	A	09	P	S	A	-A
BASIC SERIES	L- NICKEL PLATING	A-20 SIZE CONTACT (STANDARD DENSITY)	09,15,25 & 37 - STANDARD DENSITY LAYOUT	P-PIN CONTACT(MACHINED)	F-PIN CONTACT(STAMPED)	S-SOLDER	OMIT FOR NO ACCESSORIES
							A- JACKSCREW 4-40UNC
							B- JACKPOST 4-40UNC
							OMIT FOR STANDARD GOLD PLATING
							A-GOLD FLASH ON CONTACT

THIS DOCUMENT IS SOLE PROPERTY OF TURBO INDIA AND IS ISSUED IN STRICT CONFIDENCE THAT IT WILL NOT BE REPRODUCED IN ANY WAY OR USED TO SOLICIT BUSINESS OF A COMPETITIVE NATURE. DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED UNLESS WRITTEN CONSENT IS OBTAINED FROM THIS DOCUMENT IS SUITABLE FOR ENGINEERING EVALUATION AND MAY BE USED IN TECHNICAL SPECIFICATIONS.

MATERIAL:	---
SURFACE AREA:	---
EST. WEIGHT:	---
DRAWN:	MS
CHECKED:	SSC
APPROVED:	SSC
DATE:	25-01-2023

UNLESS OTHERWISE NOTED:
DIMENSIONS ARE IN MM :
FRACTION ARE ± 1/16
.XX DECIMALS ARE ± .25
.XXX DECIMALS ARE ± .07
ANGLES ARE ± 2°
DO NOT SCALE THIS DRAWING

DESCRIPTION: DSUB PLUG CONNECTOR SOLDER TYPE STANDARD DENSITY	
DRAWING NUMBER: CRD-TBDSC-LAXXPS	REVISION: 0
SHEET 1 OF 1	