

ET-OF2162-CT-HD 21,5” Touch panel

Features

- Compact and easy to integrate with mounting from sides or top and bottom; also a VESA mount option
- Optional touch technologies include: PCAP
- Worldwide agency approvals
- One year standard warranty

Applications

- Information Kiosk
- Game and Entertainment
- Industrial Automation
- Self-checking service



Specifications

Products Model	ET-OF2162-CT-HD
Description	21.5"16:9 Multitouch Capacitive Open Frame Touch Panel"
Case/Bezel Color	Steel/Black
Display Size	21.5inch 16:9 Active Matrix TFT LCD
Useful Screen Area	478mm x 269.5mm
Optimal Resolution	1920 x 1080@60Hz
Color Depth	8bit, 16.7 Million colors
Brightness	250cd/m ²
Contrast Ratio	1000:1 (Typical)
Viewing Angle(CR≥10)	Right/Left 89°/89° Up/Down 89°/89°
Video Input Format	VGA, DP, HDMI Option
Input Video Signal Connector	VGA, DP, HDMI Option
On Screen Display(OSD)	Controls(back): On/Off, Menu, Left, Right, Auto
Backlight Lamp Life	50000hrs
Touch Technology	Project Capacitive Multitouch Touch Technology
Touch Point	Standard 10 point, Max 40 point (option)
Touch Port Interface	USB or RS232 Serial
Touch Cover Glass	2mm Physical Tempered Anti-vandal Glass (AR, AG option)
Support OS	HID-Mode: Windows 7/8/10, Linux, Android, Mac etc.
Mounting Options	VESA Mount 75x75 and 100x100, Four side bracket option
Power Supply	External Adapter: 100-240V AC, 50-60Hz
Temperature Range	Operating: 0°C to 50°C; Storage: -20°C to 60°C
Humidity Range (no condensing)	Operating: 20%-80%; Storage: 10%-90%
Dimension	533.6mm x 32.1mm x 41.2mm
Warranty	1 year
Agency Approvals	CCC, FCC, CE, RoHS