



SL NO	SHELL SIZE	A	B
1	09	30.80	25.00
2	15	39.15	33.30
3	25	53.05	47.00
4	37	69.30	63.50

PART NUMBER LOGIC

TBDSC-

L

A

09

S

S

A

-A

BASIC SERIES

L- NICKEL PLATING

CONTACT SIZE

A-20 SIZE CONTACT (STANDARD DENSITY)

INSERT ARRANGMENT

09,15,25 & 37 - STANDARD DENSITY LAYOUT

S-SOCKET CONTACT (MACHINED)

G-SOCKET CONTACT (STAMPED)

S -SOLDER

OMIT FOR NO ACCESSORIES

A- JACKSCREW 4-40UNC

B- JACKPOST 4-40UNC

OMIT FOR STANDARD GOLD PLATING

A-GOLD FLASH ON CONTACT

NOTE :

- 1. SHELL : PLATED STEEL
- 2. INSULATOR : THERMOPLASTIC (PBT)
- 3. CONTACT : COPPER ALLOY (GOLD PLATED)
- 4. CURRENT RATING : 7.5AMP
- 5. DIELECTRIC : 1000Vrms
- 6. INSULATION RESISTANCE : 1000MΩ Min (at 500V DC)

THIS DOCUMENT IS SOLE PROPERTY OF TURBO INDIA.AND IS ISSUED IN STRICT CONFIDENCE THAT IT WILL NOT BE REPRODUCED IN ANY WAY OR USED TO SOLICIT BUSINESS OF A COMPETITIVE NATURE. DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED UNLESS WRITTEN CONSENT IS OBTAINED FROM THIS DOCUMENT IS SUITABLE FOR ENGINEERING EVALUATION AND MAY BE USED IN TECHNICAL SPECIFICATIONS.	MATERIAL:	---	UNLESS OTHERWISE NOTED:	DESCRIPTION: DSUB RECEPTACLE CONNECTOR SOLDER TYPE STANDARD DENSITY	
	SURFACE AREA:	---			
	EST. WEIGHT:	---			
	DRAWN:	MS	<b>DIMENSIONS ARE IN MM :</b>  FRACTION ARE ± 1/16  .XX DECIMALS ARE ± .25 .XXX DECIMALS ARE ± .07  ANGLES ARE ± 2°  DO NOT SCALE THIS DRAWING	DRAWING NUMBER: CRD-TBDSC-LAXXSS	
	CHECKED:	SSC		REVISION: 0	
	APPROVED:	SSC		SHEET 1 OF 1	
	DATE:	25-01-2023			