



DLC70A (.055" x .055")

◆ Product Features

High Q, High Power, Low ESR/ESL, Low Noise, High Self-Resonance, Ultra-Stable Performance.

◆ Product applications

Typical Functional Applications: Tuning, Bypass, Coupling, Feedback, D.C. Blocking and Impedance Matching.


Typical Circuit Applications: UHF/Microwave RF Power Amplifiers, Mixers, Oscillators, Low Noise Amplifiers, Filter Networks, Timing Circuits and Delay Lines.

◆ DLC70A Capacitance Table

Cap.pF	Code	Tol.	Rated WVDC	Cap.pF	Code	Tol.	Rated WVDC	Cap.pF	Code	Tol.	Rated WVDC	Cap.pF	Code	Tol.	Rated WVDC		
0.1	0R1		150V Code 151 or 300V Code 301	2.4	2R4	A, B, C, D	150V Code 151 or 300V Code 301	20	200	F, G, J	150V Code 151 or 300V Code 301	160	161	F, G, J	150V Code 151		
0.2	0R2			2.7	2R7				22			220				180	181
0.3	0R3			3.0	3R0				24			240				200	201
0.4	0R4			3.3	3R3				27			270				220	221
0.5	0R5			3.6	3R6				30			300				240	241
0.6	0R6			3.9	3R9				33			330				270	271
0.7	0R7			4.3	4R3		36	360		300	301						
0.8	0R8			4.7	4R7		39	390		330	331						
0.9	0R9			5.1	5R1		43	430		360	361						
1.0	1R0	A, B, C, D		5.6	5R6	B, C, J	47	470		390	391						
1.1	1R1				6.2		6R2		51	510		430	431				
1.2	1R2				6.8		6R8		56	560		470	471				
1.3	1R3				7.5		7R5		62	620		510	511				
1.4	1R4				8.2	8R2		68	680		560	561					
1.5	1R5				9.1	9R1		75	750		620	621					
1.6	1R6				10	100		82	820		680	681					
1.7	1R7				11	110		91	910		750	751					
1.8	1R8				12	120	F, G, J	100	101		820	821					
1.9	1R9			13	130			110	111		910	911					
2.0	2R0		15	150		120		121		1000	102						
2.1	2R1		16	160		130		131									
2.2	2R2		18	180		150	151										

Remark: special capacitance, tolerance and WVDC are available, consult with DALICAP.

◆ **Part Numbering**





Code	A	B	C	D	F	G	J
Tolerance	± 0.05pF	± 0.1pF	± 0.25pF	± 0.5pF	± 1%	± 2%	± 5%

Note: Tolerance of ± 0.02pF is a possibility. Please contact Dalicap

◆ **DLC70A Capacitor Dimensions**

unit:inch(millimeter)

Series	Term. Code	Type / Outlines	Capacitor Dimensions				Plated Material
			Length (L _c)	Width (W _c)	Thickness (T _c)	Overlap (B)	
DLC70A	W	 Chip	.055	.055	.057 (1.45) max	.020 (0.51) max	100% Sn Solder over Nickel Plating
	L		+ .015~ -.010 (1.40+ 0.38~ -0.25)	± .010 (1.40 ± 0.25)			90 Sn10Pb Solder over Nickel Plating
DLC70A	P (Non-Mag)	 Chip (Non-Mag)					100% Sn Solder over Copper Plating

Note: Non-Mag is no magnetism.



◆ Performance

Item	Specifications
Quality Factor (Q)	greater than 10,000 at 1 MHz
Insulation Resistance (IR)	10 ⁵ Megohms min. @ +25°C at rated WVDC. 10 ⁴ Megohms min. @ +125°C at rated WVDC.
Rated Voltage	See Rated Voltage Table
Dielectric Withstanding Voltage (DWV)	250% of Rated Voltage for 5 seconds.
Operating Temperature Range	-55°C to +200°C
Temperature Coefficient (TC)	0 ± 30 ppm/°C (-55°C to +175°C)
Capacitance Drift	± 0.02% or ± 0.02pF, whichever is greater.
Piezoelectric Effects	None
Termination Type	See Termination Type Table


Capacitors are designed and manufactured to meet the requirements of MIL-PRF-55681 and MIL-PRF-123.

◆ Environmental Tests


Item	Specifications	Method
Thermal Shock	DWV: the initial value IR: Shall not be less than 30% of the initial value Capacitance change: no more than 0.5% or 0.5pF, whichever is greater.	MIL-STD-202, Method 107, Condition A. At the maximum rated temperature(-55°C and 200°C) stay 30 minutes. The time of removing shall not be more than 3 minutes. Perform the five cycles.
Moisture Resistance		MIL-STD-202, Method 106.
Humidity (steady state)	DWV: the initial value IR: the initial value Capacitance change: no more than 0.3% or 0.3pF, whichever is greater.	MIL-STD-202, Method 103, Condition A, with 1.5 Volts D.C. applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours minimum.
Life	IR: Shall not be less than 30% of the initial value Capacitance change: no more than 2.0% or 0.5pF, whichever is greater.	MIL-STD-202, Method 108, for 2000 hours, at 200°C. 200% Rated voltage D.C. applies

◆ **DLC70A Performance Curve**


ESR vs Capacitance




Q vs Capacitance




ESR vs Capacitance



Q vs Capacitance



DLC70A Horizontal First Series Resonance (FSRs)



Definitions and Measurement Conditions

For a capacitor in a series configuration, i.e., mounted across a gap in a microstrip trace, with 50-Ohm source and termination resistances, the First Series Resonance, FSR, is defined as the lowest frequency at which the imaginary part of the input impedance, $Im[Z_{in}]$, equals zero when reference planes are at the sample edges.

The FSR shall be considered as undefined (gap in plot above) if, over the measured or model-validated frequency range: (a) $Im[Z_{in}]$ never reaches zero; or, (b) at frequencies lower than that at which $Im[Z_{in}] = 0$, $Im[Z_{in}]$ is not monotonic with frequency and/or the real part of the input impedance, $Re[Z_{in}]$, deviates more than once from monotonicity.


FSR is dependent on internal capacitor structure; substrate thickness and dielectric constant; capacitor orientation, as defined above; and mounting pad dimensions.

The measurement conditions are: substrate -- Rogers RO4350; substrate dielectric constant = 3.66; horizontal mount substrate thickness (mils) = 25; gap in microstrip trace (mils) = 15; horizontal mount microstrip trace width (mils) = 55. Reference planes at sample edges.

All data has been derived from electrical models created by Modelithics, Inc., a specialty vendor contracted by Dalicap. The models are derived from measurements on a large number of parts disposed on several different substrates.

◆ **DLC70A Performance Curve**

DLC70A Horizontal First Parallel Resonance(FPRs)




Definitions and Measurement conditions:

For a capacitor in a series configuration, i.e., mounted across a gap in a microstrip trace, with 50-Ohm source and termination resistances, the First Parallel Resonance, FPR, is defined as the lowest frequency at which a suckout or notch appears in [S21]. It is generally independent of substrate thickness or dielectric constant, but does depend on capacitor orientation. A horizontal orientation means the capacitor electrode planes are parallel to the plane of the substrate; a vertical orientation means the electrode planes are perpendicular to the substrate.

The measurement conditions are: substrate -- Rogers RO4350; substrate dielectric constant = 3.66; horizontal mount substrate thickness (mils) = 25; gap in microstrip trace (mils) = 15; horizontal mount microstrip trace width (mils) = 55. Reference planes at sample edges.

All data has been derived from electrical models created by Modelithics, Inc., a specialty vendor contracted by Dalicap. The models are derived from measurements on a large number of parts disposed on several different substrates.

Current Rating vs Capacitance




The current depends on voltage limited:

$$I = \frac{\sqrt{2}}{2} I_{peak} = \frac{\sqrt{2}}{2} \times \frac{V_{rated}}{X_C} = \sqrt{2\pi f C V_{rated}}$$

The current depends on power dissipation limited: $I = \sqrt{\frac{P_{dissipation}}{ESR}}$

Current Rating vs Capacitance




Note: If the thermal resistance of mounting surface is 40°C/W.

then a power dissipation of 1.5 W will result in the current limited

we can calculate the current limited: $I = \sqrt{\frac{P_{dissipation}}{ESR}}$

◆ **Tape & Reel Specifications**

Orientation	EIA	A0	B0	K0	W	P0	P1	T	F	Qty/reel	Tape Material
Horizontal	0505	1.38	1.68	0.98	8.00	4.00	4.00	0.22	3.50	3000	Plastic
Vertical	0505	1.10	1.60	1.40	12.00	4.00	4.00	0.30	5.50	2000	Plastic



◆ **Design Kits**

These capacitors are 100% RoHS. Kits are available in Magnetic and Non-Magnetic that contain 10(ten) pieces per value;16 values per kit.

Design Kit	Description (pF)	Values (pF)	Tolerance
DKDLC70A01	0.1 - 2.0	0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0, 1.1, 1.2, 1.5,	± 0.10pF
		1.6, 1.8, 2.0	± 0.25pF
DKDLC70A02	1.0 - 10	1.0, 1.2, 1.5, 1.8, 2.0, 2.2, 2.4, 2.7,	± 0.10pF
		3.0, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2	± 0.25pF
		10	± 5%
DKDLC70A03	10 - 100	10, 12, 15, 18, 20, 22, 24, 27, 30, 33, 39, 47, 56, 68, 82, 100	± 5%
DKDLC70A04	100 - 1000	100, 120, 150, 180, 200, 220, 240, 270, 300, 330, 390, 470, 560, 680, 820, 1000	± 5%
DKDLC70A05	0.1 - 2.0 Non-magnetic	0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0, 1.1, 1.2, 1.5,	± 0.10pF
		1.6, 1.8, 2.0	± 0.25pF
DKDLC70A06	1.0 - 10 Non-magnetic	1.0, 1.2, 1.5, 1.8, 2.0, 2.2, 2.4, 2.7,	± 0.10pF
		3.0, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2	± 0.25pF
		10	± 5%
DKDLC70A07	10 - 100 Non-magnetic	10, 12, 15, 18, 20, 22, 24, 27, 30, 33, 39, 47, 56, 68, 82, 100	± 5%
DKDLC70A08	100 - 1000 Non-magnetic	100, 120, 150, 180, 200, 220, 240, 270, 300, 330, 390, 470, 560, 680, 820, 1000	± 5%

