



SL NO	SHELL SIZE	A	B
1	09	30.80	25.00
2	15	39.15	33.30
3	25	53.05	47.00
4	37	69.30	63.50

**PART NUMBER LOGIC**

TBDSC-	L	A	09	S	C
<b>BASIC SERIES</b>	<b>L- NICKEL PLATING</b>	<b>CONTACT SIZE</b>	<b>INSERT ARRANGMENT</b>	<b>S-SOCKET CONTACT</b>	<b>C - CRIMP</b>
		<b>A-20 SIZE CONTACT (STANDARD DENSITY)</b>	<b>09,15,25 &amp; 37 - STANDARD DENSITY LAYOUT</b>		
				<b>B- WITHOUT CRIMP SOCKET CONTACT</b>	

**NOTE :**

1. SHELL : PLATED STEEL
2. INSULATOR : THERMOPLASTIC (PBT)
3. CONTACT : COPPER ALLOY (GOLD PLATED)
4. CURRENT RATING : 7.5AMP
5. DIELECTRIC : 1000Vrms
6. INSULATION RESISTANCE : 1000MΩ Min (at 500V DC)

THIS DOCUMENT IS SOLE PROPERTY AND IS ISSUED IN STRICT CONFIDENCE THAT IT WILL NOT BE REPRODUCED IN ANY WAY OR USED TO SOLICIT BUSINESS OF A COMPETITIVE NATURE. DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED UNLESS WRITTEN CONSENT IS OBTAINED FROM TURBO INDIA. THIS DOCUMENT IS SUITABLE FOR ENGINEERING EVALUATION AND MAY BE USED IN TECHNICAL SPECIFICATIONS.	MATERIAL:	---	UNLESS OTHERWISE NOTED:  <b>DIMENSIONS ARE IN MM :</b>  FRACTION ARE ± 1/16  .XX DECIMALS ARE ± .25 .XXX DECIMALS ARE ± .07	DESCRIPTION: DSUB RECEPTACLE CONNECTOR CRIMP TYPE STANDARD DENSITY		
	SURFACE AREA:	---				
	EST. WEIGHT:	---				
	DRAWN:	MS	DO NOT SCALE THIS DRAWING		DRAWING NUMBER:	REVISION:
	CHECKED:	SSC			CRD-TBDSC-LAXXSC	0
APPROVED:	SSC					
DATE:	25-01-2023					